

HLL LIFECARE LIMITED

(Formerly Hindustan Latex Limited) (A Government of India Enterprise)

KANAGALA BELAGAVI DIST. PIN - 591 225 **KARNATAKA STATE**

PH.NO: 08333-279240, 279244. FAX: 08333-279245.

Website: www.lifecarehll.com E-mail: <u>purchasekfb@lifecarehll.com</u> purchasenfk@gmail.com

TENDER NO.HL:BG:PS:BDU:REACTOR:2019-20

TENDER DOCUMENT

FOR

STAINLESS STEEL REACTOR 2KL WITH CONDENSER AND RECEIVER

: 17-JUL-2019 @ 10:30 Hrs.

Last Date and Time for Receipt of Technical & Price Bid: 16-JUL-2019 up to 17:00 Hrs.

: Will be intimated later.

Date and Time of Opening of Price Bid

Date and Time of Opening of Technical Bid

NOTICE INVITING TENDER (NIT)

HLL Lifecare Limited (Formerly Hindustan Latex Ltd), India's leading Manufacturers and Marketers of Contraceptive, Health Care and Pharma Products is a Mini Ratna Company.

HLL Lifecare Limited (HLL), a PSU under the Ministry of Health & Family Welfare, Govt. of India invites Sealed & Superscribed Tenders under **Two Bid System (Technical & Price)** in the prescribed forms enclosed from Manufacturers / Authorized Dealers for the supply, erecting and commissioning of **STAINLESS STEEL REACTOR 2KL WITH CONDENSER AND RECEIVER** at our Factory site at Kanagala, Belagavi Dist (Karnataka).

Specifications and Terms & Conditions etc., are detailed in Tender Documents. NIT / Tender Documents / NIT can be had from our Office on any working day between 11:00 AM to 3:30 PM by paying ₹ 590/- only by Cash / DD (inclusive of GST @ 18%) drawn in favor of HLL LIFECARE LTD, payable at State Bank of India, NIPANI – 591 237. Further, Tender Documents can also be downloaded from our website: www.lifecarehll.com. However cost of Tender Documents i.e. ₹ 590/- only in the form of DD should be enclosed along with Technical Bid.

NAME OF THE ITEM	QTY. REQUIRED (NOS.)
STAINLESS STEEL REACTOR 2KL WITH CONDENSER AND RECEIVER. Specifications as detailed in <u>ANNEXURE AN2.</u>	01

- 1. Last Date and Time for Receipt of Technical & Price Bid: 16.07.2019 (17:00 Hrs.)
- 2. Date and Time for Opening of Technical Bid : 17.07.2019 (10:30 Hrs.)
- 3. In the event of the date/s mentioned above being declared subsequently as holiday/s for the Purchaser's Office, the due date for meeting, submission and opening of bids will be the next working day at the same venue and time.
- 4. Addendums / Amendments issued if any to this NIT / Tender Documents shall be part of this NIT / Tender Documents and shall be published in our website specified above. It is Bidders responsibility to keep themselves updated on any such Addendums / Amendments issued, if any.
- 5. In order to provide reasonable time to the Prospective Bidders to take necessary action in preparing their Tenders / Bids as per the Addendums / Amendments, HLL may, at its discretion extend the deadline for the submission of Tenders / Bids and other allied time frames, which are linked with that deadline.
- 6. Earnest Money Deposit (Refundable): Technical Bid should be accompanied with Earnest Money Deposit (EMD) in the form of Demand Draft (DD) drawn in favour of M/s. HLL Lifecare Limited payable at STATE BANK OF INDIA, NIPANI 591 237 for a sum of ₹ 25,000/- only failing which the Bid is likely to be rejected. The EMD submitted will be

- refunded to the Bidder if his Bid is not accepted or after successful completion of the order awarded, but without any interest.
- 7. Tender Cost (Non-refundable): Technical Bid should be accompanied with Tender Cost in the form of Demand Draft (DD) drawn in favour of M/s. HLL Lifecare Limited payable at STATE BANK OF INDIA, NIPANI 591 237 for a sum of ₹ 590/- only (inclusive of GST @ 18%) failing which the Bid is likely to be rejected.
- Exemption (SSI / MSE Units): Bidders interested in availing Exemption from payment of EMD should submit a Valid Copy of their Udyog Aadhaar Registration Certificate along with their Technical Bid. Technical Bids received without enclosure of Valid Copy of Udyog Aadhaar Registration Certificate will not be evaluated and summarily rejected.
- 9. Technical Bids received without enclosures of EMD & Tender Cost in the form of DD's OR a Valid Copy of Udyog Aadhaar Registration Certificate, duly filled, signed and sealed URS will not be evaluated and summarily rejected. Please note that HLL will not be responsible for any delay in submission of Tender.
- 10. Acceptance / Rejection of the Tender is entirely at the discretion of HLL.

DEPUTY GENERAL MANAGER (PURCHASE)

1) FORMATS FOR TECHNICAL BID

- a) INSTRUCTIONS TO THE BIDDERS (ANNEXURE AN1)
- b) SCOPE OF SUPPLY AND USER REQUIREMENT SPECIFICATION (ANNEXURE AN2)
- c) DECLARATION ACCEPTING TERMS AND CONDITIONS OF THE TENDER (ANNEXURE AN3)
- d) format for manufacturers authorization form (annexure ana)
- e) GENERAL CONDITIONS FORMING PART OF THE BID

2) FORMS FOR PRICE BID

a) SCHEDULE - A: PRICE BID / RATE SCHEDULE (WITH TERMS & CONDITIONS)

NOTE: Technical Bid & Price Bid forms shall be submitted in Separate Covers.

How to send the Bid:

Both the Bids i.e. Technical Bid & Price Bid shall be submitted in sealed covers separately. Technical Bid & Price Bid shall be superscribed on the respective covers in order to clearly identify between the 2 Bids. The two separately marked Bids enclosed in single sealed cover with Tender NO. Complete in all respect addressed to The Deputy General Manager (Purchase), HLL Lifecare Ltd., Kanagala - 591 225 Dist. Belagavi, Karnataka State should reach us on or before the due date and time mentioned in the NIT. Technical Bids and Price Bids those are not submitted in two separate sealed & super scribed covers are liable for rejection.

CONTENTS OF THE BIDDING DOCUMENTS:

1. Technical Bid:

- a) DD for ₹25,000/- only towards EMD / Valid Copy of Udyog Aadhaar Registration Certificate.
- b) DD for ₹590/- only towards Tender Cost / Udyog Aadhaar Registration Certificate.
- c) SCOPE OF SUPPLY AND USER REQUIREMENT SPECIFICATION (ANNEXURE AN2) duly filled, signed and sealed. Details shall be enclosed as required by us.
- d) DECLARATION ACCEPTING TERMS AND CONDITIONS OF THE TENDER (ANNEXURE AN3) (duly filled, signed and sealed on the letterhead of the Bidder firm).
- e) FORMAT FOR MANUFACTURERS AUTHORIZATION FORM (ANNEXURE AN4) (duly filled, signed and sealed on the letterhead of the Manufacturing firm).
- f) GENERAL CONDITIONS FORMING PART OF THE BID duly signed and sealed.

2. Price Bid:

a) SCHEDULE - A: Price Bid / Rate Schedule (with Terms & Conditions) duly filled, signed and sealed.

INSTRUCTIONS TO THE BIDDERS

ANNEXURE AN1

- 1. The Quotation must to be in Two Parts i.e., A. Technical Bid and B. Price Bid.
- 2. The Bidder is expected to examine all Specifications, Instructions, Forms, and Terms & Conditions given in the Bidding Documents. Failure to furnish all information required in the Bidding Documents or submission of a Bid not substantially responsive to the Bidding Documents in every respect will be at the Bidders risk and may result in rejection of the Bid.
- 3. Any clarification required will have to be obtained one week prior to the Date of opening of the Technical Bid. For any technical clarifications please feel free to contact our Mr. V.G. Rajput at mail id: rajput@lifecarehll.com OR Cell NO.09448758804.
- 4. Addendums / Amendments issued if any to this NIT / Tender Documents shall be part of this NIT / Tender Documents and shall be published in our website specified above. It is Bidders responsibility to keep themselves updated on any such Addendums / Amendments issued, if any.
- 5. In order to provide reasonable time to the Prospective Bidders to take necessary action in preparing their Tenders / Bids as per the Addendums / Amendments, HLL may, at its discretion extend the deadline for the submission of Tenders / Bids and other allied time frames, which are linked with that deadline.
- 6. Both, Technical Bid and Price Bid must be furnished in two separate sealed & super scribed covers.
- 7. Bids received after the deadline for submission shall not be considered.
- Technical Bid must be furnished as shown in the Contents of Bidding Documents @ SI. NO.1
 mentioned above and must be super scribed as "TECHNICAL BID STAINLESS STEEL REACTOR WITH
 CONDENSER AND RECEIVER Ref: Tender NO.HL:BG:PS:BDU:REACTOR:2019-20 / 18.06.2019".
- Price Bid/s must be furnished as shown in the Contents of Bidding Documents @ SI. NO.2 mentioned above i.e., in SCHEDULE A and must be super scribed as "PRICE BID STAINLESS STEEL REACTOR WITH CONDENSER AND RECEIVER Ref: Tender NO.HL:BG:PS:BDU:REACTOR:2019-20 / 18.06.2019".
- 10. Technical Bids and Price Bids those are not submitted in two separate sealed & super scribed covers are liable for rejection.
- 11. Enclose additional sheets, if necessary, to highlight the deviations from the Technical Bid and Price Bid. Provide proper reference to these additional sheets in the Technical Bid and Price Bid.
- 12. The Evaluation of the Technical Bid is carried on the Responses given in the Technical Bid.
- 13. Price Bid of a particular Bidder would be considered for opening only if their Technical Bid is qualified. The date & time of opening of Price Bid will be intimated separately.
- 14. The Price Bid of those Bidders who do not qualify will be returned unopened.
- 15. Acceptance / Rejection of the Tender is entirely at the discretion of HLL.
- 16. Bids received by FAX / E-MAIL will not be considered.

SCOPE OF SUPPLY AND USER REQUIREMENT SPECIFICATION Stainless Steel Reactor 2KL with Condenser And Receiver

ANNEXURE AN2

SL. NO.	SCOPE OF SUPPLY – The Project is a TURNKEY TYPE and should cover the following		
1.	SS Reactor with Condenser and Receiver: Manufacture, Supply, loading & unloading at HLL, Erection, Installation, Commissioning as per detailed specification given in the document.		
2.	Care has to be taken by manufacturer to ensure that all the used materials for manufacturing are compatible to our process.		
3.	Piping for Utilities from Reactor to Utility Point will be in Supplier's Scope.		
4.	Party has to include any kind of civil work in their scope.		
5.	The Supplier has to arrange for Manpower, Tools and Consumables including fasteners (MOC SS 316). All Electrical Wiring, Internal to the Machine, as per current Electricity Rules are in the Supplier's scope and only Incoming Supply and its Termination will be in the scope of HLL.		
6.			
7.	The Party has to submit the Design Qualification Drawing (GA) and Electrical Wiring Diagram with appropriate ferrule numbering for all nodes, without omission and duplication, and documents for approval before commencement of manufacturing.		
8.	A Factory Acceptance Test should be arranged by the Supplier once the manufacturing is complete.		
9.	All Qualification documents are to be approved by HLL prior to Installation and Operational Qualification at site.		

SUPPLIER'S NAME:

CLIENT'S NAME: HLL LIFECARE LIMITED, KANAGALA

Sub: Technical Bid (URS) for Supply, Installation and Commissioning of SS REACTOR WITH CONDENSER AND RECEIVER Applicable Design Code: ASME Sec VIII Div. I (Latest addenda)

CONDENSER AND RECEIVER <u>Applicable Design Code: ASME Sec VIII Div. I (Latest addenda)</u>				
SI No	HLL Specification	Supplier Specifications		
I	TECHNICAL SPECIFICATION			
01	Equipment Name: SS Reactor			
02	Type: Impeller			
03	Capacity: 2000 liters			
04	Design Pressure (Shell): 6 Kg/cm ² /full vacuum			
05	Design Pressure (Jacket): 6 Kg/cm²/ full vacuum			
06	Design Temperature: -10 to 180oC max			
07	Operating Pressure (Shell): 4.5 Kg/cm² / full vacuum			
08	Operating Pressure (Jacket): 4 Kg/cm ² / full vacuum (for steam application)			
09	Operating Temperature: -5 °C TO 145°C			
10	Test Pressure (Shell): 7.8 Kg/cm ²			
11	Test Pressure (Jacket): 7.8 Kg/cm ²			
12	Shell inside dia: 1300 mm			
13	Height: 1500 mm			
14	Jacket inside dia: 1400 mm			
15	Shell Thickness: As per Design Parameters			
16	Dished end Thickness: As per Design Parameters			
17	Jacket Thickness: As per Design Parameters			
18	Dish end Jacket Thickness: As per Design Parameters			
II	MATERIAL OF CONSTRUCTION			
01	Shell, Heads: SS316L			
02	Jacket: CS			
03	Internals: SS316L			
Ш	Support: The Reactor is provided with Four LUG Support.			
01	Refluxline size pipe = 40 NB			
02	With U bend and valve pipe MOC: S.S 316L			
03	With lantern Assembly, Stuffing Box, Bearing Housing, With Bearing Gland Pusher, With Gun metal Bush for cooling arrangement. (To be considered in Agitator Scope)			
04	Temperature Sensor line is to be made 1 inch size on the topside Reactor.			
05	Lubricants Detail: VG / Servo Mesh 320 for Gear Box.			
06	Insulation of Jacket: 100 mm (50 mm + 50 mm) thick Rock Wool / PUF Insulation with 120 kg / cm ³ density with \$\$S304 Cladding (12 Gauges with screwed construction).			
09	Reactor Volume Indicator.			
01	INSTRUMENTATION			
01	Compound Gauge (Reactor Shell Side): 1 NO.			
02	Temperature Gauge (Reactor Shell Side): 1 NO.			
03	Pressure Gauge (Reactor Jacket Side): 1 NO.			
04	Safety Valve (Reactor Shell Side): 1 NO.			

05	Safety Valve (Reactor Jacket Side): 1 NO.	
06	Compound Gauge (Receiver Shell side): 1 NO.	
07	Light Glass (Reactor Shell side): 1 NO.	
08	Side Glass (Reactor Shell side): 1 NO.	
09	Manhole (Reactor Shell side): 1 NO.	
10	Sampling Nozzle (Reactor Shell side): 1 NO.	
11	Thermowell Nozzle (Reactor Shell side): 1 NO.	
12	Bottom Outlet Nozzle with Ball Valve & Inline view glass	
	(Reactor Shell side): 1 NO.	
V	AGITATOR DATA SHEET	
01	Type: Flat Blade Turbine	
02	Speed: 150 rpm	
03	Shaft dia: 80 mm	
04	Number of Impellers: 4 NOS.	
05	No of Blades: 6 NOS.	
06	Impeller Sweep dia.: 420 mm	
07	Distance between Impellers: 600 mm (As per Design)	
08	MOC of Shaft: SS 316L	
09	MOC of Impeller: SS 316L	
10	Stool Top Bearing: 32212	
11	Sto11 Bottom Bearing: 32213	
12	% Solid in mixing (40%)	
VI	GEAR BOX	
01	Make: Greaves Gears	
02	Type: V 500	
03	Reduction: 10:1 Worm Reduction Gear Type – RV	
04	High Speed Coupling / Size: Direct Coupled	
05	Low Speed Coupling Bolt: Flexible Pin & Bush Coupling BC4	
06	Stuffing Box: Mechanical Seal with Cooling	
07	1. Electrical control panel will consists VFD for change the speed, Start / Stop & Protection of the Motor, Provision for Local Start / Stop, external interlocks etc duly wired control panel. It will be installed at Non Flame proof area given by HLL.	
	2. Flame proof control panel (Enclosure) will be installed near to the centrifuge machine, will have provision to start / stop the Motor, Change the speed by Potentiometer, Indicators for Motor On, Off, Trip, Inter lock failed etc Digital RPM Indicator with provision for display scaling. & Digital temperature Indicator.	
	Above both panels and accessories Design, Supply, Installation, Inter connections, Commissioning, Testing etc with all materials in vendor scope. Approval should be taken for Panels design & Bill of materials used.	
	HLL will provide Electrical Power to the control panel only.	

All Instruments / indicators / control panels / terminations / wires / glands should comply for application in flameproof gas zones II A and II B and CMRI/DGMS certificate must be produced for all such items used in flame proof area. VII MECHANICAL SEAL			
wires / glands should comply for application in flameproof gas zones II A and II B and CMRI/DGMS certificate must be produced for all such items used in flame proof area.			
gas zones II A and II B and CMRI/DGMS certificate must be produced for all such items used in flame proof area.			
produced for all such items used in flame proof area.			
01 Materials Specification: Complete Mechanical Seal with			
Sleeve Housing			
02 Type: Double Mechanical Seal			
03 Size: 3.125" – Approx.			
04 Make: Leak proof / Colossus / AES			
FLAMEPROOF MOTOR DATA SHEET			
Flame proof Motor, Type TEFC, Suitable rating: 10.0 HP(Min), 3-			
Phase, 4 Pole, 415 VAC, 50 Hz, Speed 1440 rpm, Rating			
Continuous, Make: Siemens / Crompton Greaves / Hindustan			
Motors / Bharat Bijali / ABB			
12 Motor Body Earthing: Double Earthing to Motor body with			
Copper wire of suitable size as per Standard.			
Discharge of Static Electricity: To ensure Discharge Electricity			
and entire Reactor and drums used.			
14 Specification of Static Floatric Discharge Device: Model:			
14 Specification of Static Electric Discharge Device: Model: Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality.			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality.			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m ²			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m ² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side =			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max.			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum,			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 °C max., Shell side = 40 °C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm²			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 °C max., Shell side = 40 °C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm²			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L)			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L)			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 14 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L) 09 Cooling Medium: Shell side (SS 316L) with Insulation			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L) 09 Cooling Medium: Shell side (SS 316L) with Insulation X CONDENSER INSTRUMENTATION			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET O1 Name of the Equipment: Condenser O2 Type: Shell and Tube type O3 Heat Transfer Area: 6.0 m² O4 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm O5 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. O6 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² O7 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² O8 Vapour Inlet: Tube side (SS 316L) O9 Cooling Medium: Shell side (SS 316L) with Insulation X CONDENSER INSTRUMENTATION O1 Compound Gauge: Condenser Vapor Inlet - 1 NO. Temperature Gauge: Condenser Vapor Inlet and Outlet - 1 NO.			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L) 09 Cooling Medium: Shell side (SS 316L) with Insulation X CONDENSER INSTRUMENTATION 01 Compound Gauge: Condenser Vapor Inlet - 1 NO. 02 Temperature Gauge: Condenser Vapor Inlet and Outlet - 1 NO. each 03 Compound Gauge: Condenser Vapor Outlet - 1 NO.			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L) 09 Cooling Medium: Shell side (SS 316L) with Insulation X CONDENSER INSTRUMENTATION 01 Compound Gauge: Condenser Vapor Inlet - 1 NO. 02 Temperature Gauge: Condenser Vapor Outlet - 1 NO. 03 Compound Gauge: Condenser Vapor Outlet - 1 NO. 04 Pressure Gauge: Condenser Vapor Outlet - 1 NO.			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L) 09 Cooling Medium: Shell side (SS 316L) with Insulation X CONDENSER INSTRUMENTATION 01 Compound Gauge: Condenser Vapor Inlet - 1 NO. 02 Temperature Gauge: Condenser Vapor Inlet and Outlet - 1 NO. each 03 Compound Gauge: Condenser Vapor Outlet - 1 NO. 04 Pressure Gauge: Condenser Vapor Outlet - 1 NO.			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L) 09 Cooling Medium: Shell side (SS 316L) with Insulation X CONDENSER INSTRUMENTATION 01 Compound Gauge: Condenser Vapor Inlet - 1 NO. 02 Temperature Gauge: Condenser Vapor Inlet and Outlet - 1 NO. each 03 Compound Gauge: Condenser Vapor Outlet - 1 NO. 04 Pressure Gauge: Condenser Vapor Outlet - 1 NO.			
Bond-Rite Clamp with 5 m (16Ft) cable BRC05 (Self testing clamps with and built in LED Indicators for Safety in critical operations that are prone to corrosion) Party should give successful trials for the above-mentioned functionality. IX CONDENSER DATA SHEET 01 Name of the Equipment: Condenser 02 Type: Shell and Tube type 03 Heat Transfer Area: 6.0 m² 04 Tube Details: 1" x 2020 mm L x 56 Nos x Triangular Pitched to 31.75 mm 05 Operating Temperature: Tube side = 90 ° C max., Shell side = 40 ° C max. 06 Operating Pressure: Tube side = 6.0 kg / cm² / full vacuum, Shell side - 3.0 kg / cm² 07 Test Pressure: Tube side - 9.5 kg / cm² Shell side - 5.2 kg / cm² 08 Vapour Inlet: Tube side (SS 316L) 09 Cooling Medium: Shell side (SS 316L) with Insulation X CONDENSER INSTRUMENTATION 01 Compound Gauge: Condenser Vapor Inlet - 1 NO. 02 Temperature Gauge: Condenser Vapor Inlet and Outlet - 1 NO. each 03 Compound Gauge: Condenser Vapor Outlet - 1 NO. 04 Pressure Gauge: Condenser Vapor Outlet - 1 NO.			

03	Capacity: 300 L			
04	Design Pressure (Shell): 2 kg/ cm ²			
05	Design Pressure (Jacket): 5 kg/ cm ²			
06	Design Temperature: 180 °C max			
07	Operating Pressure (Shell): Atmosphere			
08	Operating Pressure (Jacket): 3.0 kg / cm ²			
09	Operating Temperature: 140 °C max			
10	Test Pressure (Shell) [Kg/ cm ²]: 2.6 kg/ cm ²			
11	Test Pressure (Jacket) [Kg/ cm²]: 6.5 kg/ cm²			
12	Shell inside dia (mm): 700 mm			
13	Height (mm): 800 mm			
14	Jacket inside dia (mm): 800 mm			
15	Shell Thickness (mm): As per Design Parameters			
16	Dished end Thickness (mm): As per Design Parameters			
17	Jacket Thickness (mm): As per Design Parameters			
18	Dish end Jackets Thickness (mm): As per Design Parameters			
19	Light and Sight Glass (mm): 100 mm			
20	Insulation of Jacket: 100 mm (50 mm + 50 mm) thick Rock			
	Wool / PUF Insulation with 120 kg / cm ³ density with \$\$304			
2411	Cladding (12 Gauges with screwed construction).			
XII	RECEIVER INSTRUMENTATION			
01	Compound Gauge: Receiver Shell Side - 1 NO.			
02	Temperature Gauge: Receiver Shell Side - 1 NO.			
03	Pressure Gauge: Receiver Jacket Side - 1 NO.			
04	Light Glass: Receiver Shell Side - 1 NO.			
05	Side Glass: Receiver Shell Side - 1 NO.			
06	Bottom Outlet Nozzle with Ball Valve: Receiver Shell Side - 1 NO.			
07	Level Indicator			

We have read and understood the above Specifications and agree to abide by the same.

Name and Address of the Bidder along with details of the GST Registrations:			
Authorized Signatory's Name, Designation and Signature for all correspondence			

All the information provided herein is true & correct.

List of E	inclosures to Technical Bid:
1.	
2.	
3.	
4.	
5.	
SPECIA	L NOTE:
1.	The Bid should include specific answers strictly with respect to our Tender Specifications and Specification deviation if any, should be highlighted with clarifications. Otherwise, the Bid will not be considered. Wherever space is insufficient, please enclose separate sheets.
2.	The Bid along with its enclosures should be furnished with Original only. Bid received by FAX / E-MAIL will not be considered.
3.	The Bidder should furnish the quantitative values with respect to specified values in the Technical Specification of the Quote clearly instead of mentioning either "Complied", "Agreed" or "Confirmed" etc., otherwise, the Tender Quote is liable to be Rejected.
Place: Date:	Signature of the Bidder Name, Seal and Address of the Bidder

DECLARATION ACCEPTING TERMS AND CONDITIONS OF THE TENDER ANNEXURE AN3

Date
To: HLL Lifecare Limited (A Govt. of India Enterprise) Kanagala – 591225. Tal: Hukkeri, Dist: Belagavi, Karnataka, India
Dear Sirs,
Ref. Your TE document Nodated
We, the undersigned have examined the above-mentioned TE document, including amendment/corrigendum No, dated (if any), the receipt of which is hereby confirmed. We now offer to supply and deliver (Description of goods and services) in conformity with your above referred document for the sum as shown in the price schedule(s), attached herewith in a separate envelope and made part of this tender.
If our tender is accepted, we undertake to supply the goods and perform the services as mentioned above, in accordance with the delivery schedule specified in the List of Requirements.
We further confirm that, if our tender is accepted, we shall provide you with a performance security of required amount in an acceptable form, for due performance of the contract. We agree to keep our tender valid for the period mentioned in the tender notification. We also accordingly confirm to abide by this tender up to the aforesaid period and this tender may be accepted any time before the expiry of the aforesaid period. We further confirm that, until a formal contract is executed, this tender read with your written acceptance thereof within the aforesaid period shall constitute a binding contract between us.
We further understand that you are not bound to accept the lowest or any tender you may receive against your above-referred tender enquiry.
We confirm that we do not stand deregistered/banned/blacklisted by any Govt. Authorities.
We confirm that we fully agree to the terms and conditions specified in above mentioned TE document, including amendment/ corrigendum if any
(Signature with date)
(Name and Designation) Duly Authorized to sign Tender for and on behalf of M/s
Office Seal

FORMAT FOR MANUFACTURERS AUTHORIZATION FORM

ANNEXURE AN4

Do	ate
(A Kc Ta	: L Lifecare Limited Govt. of India Enterprise) nagala – 591225. I: Hukkeri, Dist: Belagavi, rnataka, India
De	ear Sirs,
Re	f. Your TE document Nodated
hc M, pr	who are proven and reputable manufacturers (name and description of the goods offered in the tender) (ving factories at, hereby authorize (s, name and address of the agent) to submit a tender, occess the same further and enter into a contract with you against your requirement as intained in the above referred TE documents for the above goods manufactured by us.
te	e further confirm that no supplier or firm or individual other than M/s. (name and address of the above agent) is authorized to submit a nder, process the same further and enter into a contract with you against your requirement contained in the above referred TE documents for the above goods manufactured by us.
C	e also hereby extend our full warranty, CMC as applicable as per General Conditions of ontract, read with modification, if any, for the goods and services offered for supply by the bove firm against this TE document.
Yc	urs faithfully,
_	gnature with date, name and designation] for and on behalf of 's
[N	ame & address of the manufacturer]
<u>Nc</u>	o <u>te:</u>
1.	This letter of authorization should be on the letterhead of the manufacturing firm and should be signed by a person competent and having the power of attorney to legally bind the manufacturer.
2.	Original letter may be sent.

GENERAL CONDITIONS FORMING PART OF BID

This is Two-Bid System comprising of:

- A) Technical Bid B) Price Bid
- 1. Both the Bids shall be submitted in sealed covers separately. Tender NO. of Technical Bid and Price Bid shall be superscribed on the respective covers in order to clearly identify between the 2 Bids. The two separately marked Bids enclosed in single sealed cover with the respective Tender NO. mentioned thereon, complete in all respect, addressed to THE DEPUTY GENERAL MANAGER (PURCHASE) HLL LIFECARE LTD., KANAGALA 591 225, DIST- BELAGAVI, KARNATAKA STATE, INDIA should reach us on or before the due date and time mentioned in the NIT. The Purchaser shall not be responsible for postal delay if any, in the delivery of the Bidding Document or non-receipt of the same.
- 2. EMD of ₹ 25,000/- only should be remitted by DD only, drawn in favor of HLL Lifecare Limited, payable at State Bank of India, Nipani 591 237 and shall be enclosed along with the Technical Bid. However, SSI / MSE Units interested in availing Exemption from payment of EMD and Tender Cost should submit a Valid Copy of their Udyog Aadhaar Registration Certificate along with their Technical Bid.
- 3. Bids received after the deadline for the submission will not be considered.
- 4. Un-sealed Tenders received are liable to be rejected and this will be on sole risk of Bidders.
- 5. The Bidder is expected to examine all Specifications, Instructions, Forms, Terms & Conditions given in the Tender Document.
- 6. The Tender should be complete in all respects & incomplete Tenders are liable to be rejected.
- 7. Description and Specification should be the same as given in the Enquiry / Tender / NIT.
- 8. Any change in the Description or Specification shall be at the specific instruction of HLL. In case an offer of a brand is being made, the offer should be as per the Description given in the NIT / Tender and the brand name to be given in bracket. A Separate Sheet should be attached.
- 9. HLL Lifecare Limited reserves the right to split up the order for the entire quantity on more than a supplier and also reserves the right to accept or reject the offer without assigning any reason.
- 10. Addendums / Amendments issued if any to this NIT / Tender Documents shall be part of this NIT / Tender Documents and shall be informed to the Bidders who have purchased the NIT / Tender Documents or shall be published in our website. The Bidders are advised to check our website specified above to download the Addendums / Amendments issued, if any.
- 11. THERE WILL NOT BE ANY POST TENDER NEGOTIATION EXCEPT WITH 1st LOWEST.

GENERAL CONDITIONS FORMING PART OF BID

- 12. Security Deposit of 5% of the total order value should be deposited.
- 13. The Parties have to abide by Delivery Schedule strictly. HLL Lifecare Limited reserves the right to impose Penalty @ 0.5% value of the delayed material per week of delay subject to a maximum of 7.5% of the value of the supply defaulted if material is delayed beyond the due date and accepted by the Company.
- 14. Acceptance of the delayed supplies subject to Penalty Clause is solely at the discretion of the Company (HLL Lifecare Limited).
- 15. Rejected material should be taken back and replaced with supplier's cost within 7 (seven) days.
- 16. Dispatch Documents like Delivery Note, Packing List and Invoice should contain the following details:
 - a) Purchase Order NO. / Supply Order NO. & Date.
 - b) Description of Items as contained in the Purchase Order.
 - c) Quantity Dispatched
 - d) Total NO. of Packages.
- 17. The following information shall be stenciled or labeled on the exterior of the packing in bold letters, clearly visible, at least 50 mm high with waterproof ink.
 - A. Instruction for Storage and Handling.
 - B. Name and Address of Manufacturer.
 - C. Companies Address in full.
 - D. All Packages should be numbered and it should appear on top of the packages serially.
- 18. The Jurisdiction of any disputes, suits and proceedings arising out of this NIT / Tender shall be only in the Courts of Hukkeri Taluk, Belagavi Dist. / Trivandrum.

19. Indemnity Clause

If the Supplier fails to execute the order within the time prescribed for the delivery of goods ordered or violates or infringes the existing rates as mentioned and agreed to in the Purchase Order the Supplier shall and will indemnify the Company against all losses or damages whatsoever to be incurred or sustained including the legal cost or expenses incurred by the Company by reason of non-delivery of goods at agreed quantity and rate within the time specified in the Purchase Order. The Company will initiate legal action if the Supplier fails to execute the Purchase Order as per the schedule in the Purchase Order for the actual loss suffered or 5% of the total order value whichever is higher along with costs.

- 20. HLL Lifecare Limited shall fix the criteria for responsiveness of a Bid based on critical factors in the Tender Document. Bids pronounced non-responsive by HLL shall be summarily rejected.
- 21. Suppression of facts will disqualify the Bidder.

GENERAL CONDITIONS FORMING PART OF BID

- 22. Payment Terms: Our intention is to make payment by cheque within 30 days of receipt; inspection and acceptance of the material and cheque will be forwarded to parties through Speed Post.
- 23. HLL Lifecare Limited reserves the right to qualify or not a Tender without assigning any reasons. The decision of HLL will be final and no correspondence will be entertained in this regard.
- 24. The Tender is liable to be suspended or cancelled at anytime at the discretion of the Company without assigning any reasons.

We have read and understood the above Conditions and agree to abide by the same.

Place: Signature of the Bidder

Date: Name, Seal and Address of the Bidder

SCHEDULE - A: PRICE BID

ITEM: SUPPLY, INSTALLATION AND COMMISSIONING OF STAINLESS STEEL REACTOR 2KL WITH CONDENSER AND RECEIVER – Qty: 01 NO.

SL.	Scope of Supply / Work		GST		Total
NO.	Scope of Supply / Work	Basic Price	%	Amt	Total
1	Reactor with Complete Attachments and Accessories				
2	Condenser with Complete Attachments and Accessories				
3	Receiver with Complete Attachments and Accessories				
4	Piping including all the Materials & Consumables				
5	Civil Work / Platform or Base Fabrication as required with Material				
6	Packing Charges				
7	Freight Charges				
8	Insurance Charges				
9	Loading / Unloading Charges				
10	Installation, Erection & Commissioning Charges				
GRAI	ND TOTAL F.O.R. HLL STORES KANAGALA				
Rupe	es in words				

DELIVERY PERIOD	(FROM THE DATE OF ORDER):	

TERMS AND CONDITIONS OF PRICE BID:

- 1. Please furnish your **GSTIN**. Enclose supporting document.
- 2. **HSN Code & Rate (%) of GST applicable** shall be clearly mentioned.
- 3. The rate should be inclusive of all for Supply, Installation & Commissioning on TURN KEY BASIS.
- 4. Civil Works, if any, required for Installation, Foundation laying etc., to be carried out by the party.
- 5. Party should take care of all Safety Measures and should obtain Work Permit from our Safety Dept. before starting the work.

- 6. In case of any damages caused to our (HLL Lifecare Limited) property by you/ your workmen while executing the above job, the Company (HLL Lifecare Limited) shall recover the cost of such damages from you.
- 7. In the event of any accident to your workmen or personnel while executing the above job in the Company's Premises (HLL Lifecare Limited), you shall pay the compensation as per the Workmen's Compensation Act and the rates framed there under.
- 8. Statutory Deductions, if any, applicable, like PF, ESI, Work Contract Tax and TDS etc., will be recovered from your payment.
- 9. There will not be any post Tender negotiation except with L1 (Lowest).
- 10. There shall not be Corrections / Overwriting in Price Bid, if so, same are to be attested.
- 11. Rate shall be quoted in the enclosed format only. Please refer SCHEDULE A: PRICE BID.
- 12. Rates quoted shall be valid for a period of one year, from the date of your Offer.
- 13. Specifications of Items are as per Notice Inviting Tender (NIT).

We have read and understood the above Conditions and agree to abide by the same.

Place: Signature of the Bidder

Date: Name, Seal and Address of the Bidder

Note: We are utilizing services of M/s. Shree Maruti Courier Services for incoming and outgoing Letters / Parcels on day-to-day basis.