

Technical drawing of a shaft assembly with dimensions and labels:


- KEY WAY** 6x3 Depth ,62 MM Length
- Bristles** 0.52 MM THK
- M6 TAPPED HOLE** 15 MM DEPTH
- SHAFT** Matl:-Aisi304
- PP WHITE CORE**

Dimensions (mm):


- Overall length: 1672
- Distance from left end to first bristle set: 1550
- Distance between bristle sets: 1500
- Distance from last bristle set to right end: 25
- Distance from left end to key way: 62
- Distance from key way to first bristle set: 25
- Distance from last bristle set to right end: 60
- Distance from left end to first bristle set: 12
- Distance between bristle sets: 10mm Pitch
- Distance from last bristle set to right end: 12

Other dimensions and features:

- Shaft diameter: Ø80
- Key way diameter: Ø30
- Distance from left end to key way: Ø18
- Distance from last bristle set to right end: Ø20
- Distance from left end to first bristle set: Ø18
- Distance from last bristle set to right end: Ø20
- Distance from left end to first bristle set: Ø18
- Distance from last bristle set to right end: Ø20



NO.OF BRISTLES IN EACH HOLE = 52 Nos.
66 GRADE DUPONT NYLON BRISTLE DIA.0.52MM THK
148 HOLES MINIMUM ON LENGTHWISE.
HORIZONTAL PITCH =10 mm & CIRCULAR PITCH = 10 mm
25 HOLES MINIMUM ON CIRCULAR SECTION.
ZIG - ZAG ARRANGEMENT.
TEST CERTIFICATE TO BE PRODUCED FOR NYLON BRISTLES.

MATERIAL:		HLL LIFECARE LIMITED.		NO:10FF1	
PP White,NYLON6,AISI 304		Thiruvananthapuram-5			
DRAWN BY:		FREDY JOSEPH	TITLE:- BEAD BRUSH WITH PP White CORE (Large) (MODIFIED)		
CHECKED BY:		FAHD ALI (MGR)			
APPROVED BY:		FAHD ALI (MGR)			
DATE:		28-07-2018			
SCALE:		NTS			
ALL DIMENSIONS ARE IN M.M			Drg .no:-HLL-B-244-00		
			SHEET.NO:-10FF.1		REV : 01 DATE : 23.07.2022