




































NOTE : THIS P&ID IS ONLY FOR INFORMATION. ACTUAL P&ID HAVE TO BE PROVIDED BY THE VENDOR



| VESSEL DETAILS | |
|-------------------------|-----------------------|
| G.V | 500L |
| W.V | 400L |
| QTY | 1 No. |
| H/D RATIO | 1.5:1.0 |
| MOC PRODUCT CONTACT | SS316L |
| MOC PRODUCT NON-CONTACT | SS304 |
| JACKET | HOLLOW TYPE |
| INSULATION | CERAMIC WOOL |
| BAFFLE | 1 No. |
| AGITATOR | BOTTOM MAGNETIC MIXER |
| LEG | 3 NOS |

| | | |
|---|---|---------------------------------------|
|  |  | CLIENT SCOPE VENDORS SCOPE |
| |  | CHWS |
| |  | CHWR |
| |  | PLANT STEAM |
| |  | WFI |
| |  | CIP |
| |  | PURE STEAM |
| |  | DRAIN |
| |  | BLOWASTE DRAIN |
| |  | COMPRESSED AIR |
| |  | MANUAL BALL VALVE |
| |  | PRESSURE/SAFETY RELIEF VALVE |
| |  | MANUAL DIAPHRAGM VALVE |
| |  | ACTUATED BALL VALVE |
| |  | PNEUMATIC ACTUATED DIAPHRAGM VALVE |
| |  | DIAPHRAGM PRESSURE GAUGE |
|  | STEAM TRAP | |
|  | FLOAT TRAP | |
|  | BOURDON PRESSURE GAUGE | |
|  | CONDUCTIVITY SENSOR | |
|  | TRI CLOVER CLAMP | |
|  | SPRAY BALL | |
|  | TEMPERATURE INDICATOR | |
|  | INTEGRITY CONNECTOR | |
|  | TANK BOTTOM VALVE | |
|  | PURE STEAM TO FBV | |
|  | pH SENSOR | |
|  | FLEXIBLE HOSE | |
|  | MIXER | |
|  | FLEXIBLE HOSE | |
|  | CIP CAP | |
|  | MANUAL SAMPLING VALVE | |
|  | MANUAL FLUSH BOTTOM VALVE | |

LEGEND

[illegible]